

1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

an optical integrator which is arranged in an optical path between the light source and the illumination objective plane and forms a multiple light source on the basis of the light beam from the light source; and

2. The illumination optical apparatus according to claim 1, wherein:

112

source on the basis of a light beam from the first multiple light source; and

the illumination optical apparatus further comprises a magnification-varying optical system which is arranged in an optical path between the first optical integrator and the second optical integrator and which similarly changes an entire size of the second multiple light source.

3. The illumination optical apparatus according to claim 2, wherein the aspect ratio-changing element is constructed to be rotatable about a center of an optical axis of the aspect ratio-changing element.

4. The illumination optical apparatus according to claim 2, wherein the aspect ratio-changing element includes a first aspect ratio-changing element which is arranged in the optical path between the light source and the first optical integrator and changes an angle of incidence of the incoming light beam into the first optical integrator in a first direction, and a second aspect ratio-changing element which is arranged in the optical path between the light source and the first optical integrator and changes an angle of incidence of the incoming light beam into the first optical integrator in a second direction perpendicular to the first direction.

5. The illumination optical apparatus according to

claim 2, wherein the aspect ratio-changing element includes a first prism which has a refractive surface having a concave cross section in the predetermined direction, a second prism which has a refractive surface having a convex cross section formed complementarily with the refractive surface having the concave cross section of the first prism, and a driving unit which is connected to at least one of the first prism and the second prism and moves at least one of the first prism and the second prism along an optical axis.

6. The illumination optical apparatus according to claim 5, wherein the concave cross section of the first prism has a V-shaped configuration.

7. An exposure apparatus for transforming a pattern on a mask onto a workpiece comprising:

the illumination optical apparatus according to claim 1, which illuminates the mask arranged at the illumination objective plane; and

a projection optical system which is arranged in an optical path between the mask and the workpiece and projects an image of the pattern onto the workpiece.

8. A method for producing a microdevice, comprising an exposing step of exposing the workpiece with the pattern on the mask with the exposure apparatus as defined in claim

7, and a developing step of developing the photosensitive substrate exposed in the exposing step.

9. The illumination optical apparatus according to claim 1, further comprising a guiding optical system which is arranged in an optical path between the optical integrator and the illumination objective plane and guides the light beam from the optical integrator to the illumination objective plane, and a light beam-converting element which is arranged in the optical path between the light source and the optical integrator and converts the light beam from the light source into a light beam having a predetermined cross-sectional configuration or a light beam having a predetermined light intensity distribution.

10. The illumination optical apparatus according to claim 9, wherein the aspect ratio-changing element is constructed to be rotatable about a center of an optical axis of the aspect ratio-changing element.

11. The illumination optical apparatus according to claim 9, wherein the aspect ratio-changing element includes a first aspect ratio-changing element which is arranged in the optical path between the light source and the optical integrator and changes an angle of incidence of the incoming light beam into the optical integrator in a first direction, and a second aspect ratio-changing element which

is arranged in the optical path between the light source and the optical integrator and changes an angle of incidence of the incoming light beam into the optical integrator in a second direction traverse to the first direction.

12. The illumination optical apparatus according to claim 9, wherein the aspect ratio-changing element includes a first prism which has a refractive surface having a concave cross section in the predetermined direction, a second prism which has a refractive surface having a convex cross section formed complementarily with the refractive surface having the concave cross section of the first prism, and a driving unit which is connected to at least one of the first prism and the second prism and moves at least one of the first prism and the second prism along an optical axis.

13. The illumination optical apparatus according to claim 12, wherein the concave cross section of the first prism has a V-shaped configuration.

14. An illumination optical apparatus comprising:
an illumination optical system which illuminates an illumination objective; and

a varying mechanism which is attached to the illumination optical system and varies at least one of a

size and a shape of an illumination light beam on a pupil of the illumination optical system, wherein:

the varying mechanism includes a first displacement unit which is arranged in an illumination optical path and displaces the illumination light beam symmetrically with respect to an optical axis of the illumination optical system in a first direction perpendicular to the optical axis.

15. The illumination optical apparatus according to claim 14, wherein the varying mechanism further includes a second displacement unit which is arranged in the illumination optical path and displaces the illumination light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction, and a magnification-varying optical system which is arranged in the illumination optical path and varies the size of the illumination light beam.

16. The illumination optical apparatus according to claim 15, wherein the illumination optical system includes a light shape converter which is arranged in the illumination optical path and converts the shape of the illumination light beam into a desired light beam shape and which guides the illumination light beam converted to have the desired light beam shape to the varying mechanism.

17. The illumination optical apparatus according to claim 16, wherein the light shape converter includes a first diffractive optical member which is capable of inserting the illumination optical path and converts the shape of the illumination light beam into a first light beam shape, and a second diffractive optical member which is provided exchangeably with the first diffractive optical member and which converts the shape of the illumination light beam into a second light beam shape.

18. The illumination optical apparatus according to claim 15, wherein the illumination optical system includes an optical integrator which is arranged in an optical path between the varying mechanism and the illumination objective and which uniformly illuminates the illumination objective.

19. The illumination optical apparatus according to claim 18, wherein the optical integrator is a micro fly's eye or a rod type integrator.

20. An exposure apparatus for transforming a pattern on a mask onto a workpiece comprising:

the illumination optical apparatus according to claim 14, which illuminates the mask arranged at the illumination objective plane; and

a projection optical system which is arranged in an optical path between the mask and the workpiece and projects an image of the pattern onto the workpiece.

21. A method for producing a microdevice, comprising an exposing step of exposing the workpiece with the pattern on the mask with the exposure apparatus as defined in claim 20, and a developing step of developing the photosensitive substrate exposed in the exposing step.

22. The illumination optical apparatus according to claim 14, wherein the varying mechanism further includes an annular ratio-varying unit which is arranged in the illumination optical path and converts the illumination light beam into one having an annular configuration with a desired annular ratio.

23. The illumination optical apparatus according to claim 22, wherein the varying mechanism includes a magnification-varying optical system which is arranged in the illumination optical path and varies the size of the illumination light beam.

24. The illumination optical apparatus according to claim 22, wherein the varying mechanism further includes a second displacement unit which is arranged in the illumination optical path and displaces the illumination

light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction.

25. The illumination optical apparatus according to claim 22, wherein the illumination optical system includes a light shape converter which is arranged in the illumination optical path and converts the shape of the illumination light beam into a desired light beam shape and which guides the illumination light beam converted to have the desired light beam shape to the varying mechanism.

26. The illumination optical apparatus according to claim 25, wherein the light shape converter includes a first diffractive optical member which is capable of inserting the illumination optical path and converts the shape of the illumination light beam into a first light beam shape, and a second diffractive optical member which is provided exchangeably with the first diffractive optical element and which converts the shape of the illumination light beam into a second light beam shape.

27. The illumination optical apparatus according to claim 22, wherein the illumination optical system includes an optical integrator which is arranged in an optical path between the varying mechanism and the illumination objective and which uniformly illuminates the illumination

objective.

28. The illumination optical apparatus according to claim 22, wherein the annular ratio-varying unit is a conical axicon.

29. An exposure method for exposing a workpiece with a pattern on a mask, comprising:

an illuminating step of illuminating the mask via an illumination optical system with an optical axis; and

a projecting step of projecting an image of the pattern on the mask onto the workpiece, wherein:

the illuminating step comprises displacing an illumination light beam symmetrically with respect to an optical axis of the illumination optical system in a first direction perpendicular to the optical axis on a pupil of the illumination optical system.

30. The exposure method according to claim 29, wherein the illuminating step further comprises converting the illumination light beam into one having an annular configuration on the pupil of the illumination optical system, and displacing the illumination light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction.

31. The exposure method according to claim 30, wherein the illuminating step further comprises changing a size of the illumination light beam.

32. The exposure method according to claim 30, wherein the illuminating step further comprises converting a shape of the illumination light beam into a desired light beam shape before converting the illumination light beam into one having the annular configuration.

33. The exposure method according to claim 29, wherein the illuminating step further comprises displacing the illumination light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction, and changing a size of the illumination light beam.

34. The exposure method according to claim 33, wherein the illuminating step further comprises converting a shape of the illumination light beam into a desired light beam shape before displacing the illumination light beam.

35. The exposure method according to claim 29, wherein the illuminating step further comprises converting the illumination light beam into one having an annular configuration on the pupil of the illumination optical

system, and converting an annular ratio of the converted annular illumination into a desired annular ratio.

36. The exposure method according to claim 35, wherein the illumination step further comprises changing a size of the illumination light beam.

37. The exposure method according to claim 35, wherein the illuminating step further comprises a second displacing step of displacing the illumination light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction.

38. The exposure method according to claim 35, wherein the illuminating step further comprises converting a shape of the illumination light beam into a desired light beam shape before converting the illumination light beam into one having the annular configuration.

39. The exposure method according to claim 38, wherein the light shape-converting step includes converting the shape of the illumination light beam into a first light beam shape by using a first diffractive optical member, and converting the shape of the illumination light beam into a second light beam shape by using a second diffractive optical member which is provided exchangeably with the

first diffractive optical member.

40. The exposure method according to claim 35, wherein the illuminating step comprises uniformly illuminating the illumination objective by using an optical integrator.

41. The exposure method according to claim 29, wherein:

the illuminating step further comprises a changing step of changing an illumination condition for the mask;

the changing step comprises a selecting step of selecting at least one of a first setting step of setting a first illumination condition for the illumination optical system, and a second setting step of setting a second illumination condition for the illumination optical system;

the first setting step comprises a step of converting the illumination light beam into one having an annular configuration on the pupil of the illumination optical system, a step of displacing the illumination light beam symmetrically with respect to the optical axis in the first direction which is perpendicular to the optical axis of the illumination optical system, and a step of displacing the illumination light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction; and

the second setting step comprises a step of displacing the illumination light beam symmetrically with respect to the optical axis in the first direction which is perpendicular to the optical axis of the illumination optical system, a step of displacing the illumination light beam symmetrically with respect to the optical axis in the second direction which is perpendicular to the optical axis and which intersects the first direction, and a step of changing a size of the illumination light beam.

42. The exposure method according to claim 29, wherein:

the illuminating step further comprises a changing step of changing an illumination condition for the mask;

the changing step comprises a selecting step of selecting at least one of a first setting step of setting a first illumination condition for the illumination optical system, and a second setting step of setting a second illumination condition for the illumination optical system;

the first setting step comprises a step of converting the illumination light beam into one having an annular configuration having a desired annular ratio on the pupil of the illumination optical system, and a step of changing a size of the illumination light beam; and

the second setting step comprises a step of displacing the illumination light beam symmetrically with respect to the optical axis of the illumination optical system in a

predetermined direction which is perpendicular to the optical axis, and a step of changing the size of the illumination light beam.

43. The exposure method according to claim 29, wherein:

the illuminating step further comprises a changing step of changing an illumination condition for the mask;

the changing step comprises a selecting step of selecting at least one of a first setting step of setting a first illumination condition for the illumination optical system, a second setting step of setting a second illumination condition for the illumination optical system, and a third setting step of setting a third illumination condition for the illumination optical system;

the first setting step comprises an annular ratio-varying step of converting the illumination light beam into one having an annular configuration having a desired annular ratio on the pupil of the illumination optical system, a step of displacing the illumination light beam symmetrically with respect to the optical axis of the illumination optical system in the first direction which is perpendicular to the optical axis, and a step of displacing the illumination light beam symmetrically with respect to the optical axis in a second direction which is perpendicular to the optical axis and which intersects the first direction;

the second setting step comprises a step of converting the illumination light beam into one having an annular configuration having a desired annular ratio, and a step of changing a size of the illumination light beam; and

the third setting step comprises a step of displacing the illumination light beam symmetrically with respect to the optical axis of the illumination optical system in the first direction which is perpendicular to the optical axis, a step of displacing the illumination light beam symmetrically with respect to the optical axis in the second direction which is perpendicular to the optical axis and which intersects the first direction, and a step of changing the size of the illumination light beam.

44. An exposure method for exposing a workpiece with a pattern on a mask, comprising:

an illuminating step of illuminating the mask via an illumination optical system;

a projecting step of projecting an image of the pattern on the mask onto the workpiece by using a projection optical system; and

a measuring step of measuring an optical characteristic of the projection optical system, wherein the illuminating step comprises:

an exposure condition-setting step of setting a σ value as an illumination condition to be within a range of $0.4 \leq \sigma \leq 0.95$ when the projecting step is executed; and

a measuring condition-setting step of setting the σ value as the illumination condition to be within a range of $0.01 \leq \sigma \leq 0.3$ when the measuring step is executed.

45. The exposure method according to claim 44, further comprising:

a scanning step of moving the mask and the workpiece in a scanning direction when the projecting step is executed, wherein:

the illuminating step comprises a step of forming a rectangular illumination area having a length L_s of a longitudinal direction and a length L_l of a transverse direction on the mask; and

a relationship of $0.05 < L_s/L_l < 0.7$ is satisfied.

46. An exposure apparatus for exposing a workpiece with a pattern on a mask, comprising:

an illumination optical system which is arranged in an optical path upstream of the mask and illuminates the mask; and

a projection optical system which is arranged in an optical path between the mask and workpiece and projects an image of the pattern on the mask onto the workpiece, wherein:

the illumination optical system includes an illumination condition-setting mechanism which is attached to the illumination optical system and sets a σ value as an

illumination condition to be within a range of $0.4 \leq \sigma \leq 0.95$ when the workpiece is exposed with the pattern on the mask and which sets the σ value as the illumination condition to be within a range of $0.01 \leq \sigma \leq 0.3$ when an optical characteristic of the projection optical system is measured.

47. The exposure apparatus according to claim 46, further comprising a scanning unit which moves the mask and the workpiece in a scanning direction when the workpiece is exposed with the pattern on the mask, wherein:

a relationship of $0.05 < L_s/L_l < 0.7$ is satisfied provided that L_s represents a length in a transverse direction of an illumination area formed on the mask by the illumination optical system, and L_l represents a length in a longitudinal direction of the illumination area formed on the mask by the illumination optical system.